

HAOPIN MICROELECTRONICS CO.,LTD.

注：该产品为管装，每管80PCS，每一盒为4K

Description

Passivated high commutation triacs in a plastic envelope intended for use in circuits where high static and dynamic dV/dt and high dI/dt can occur. These devices will commute the full rated ms current at the maximum rated junction temperature without the aid of a snubber.

Symbol		Simplified outline	
		 TO-252	
Pin	Description		
1	Main terminal 1 (T1)		
2	Main terminal 2 (T2)		
3	gate (G)		
TAB	Main terminal 2 (T2)		

Applications:

- ◆ Motor control
- ◆ Industrial and domestic lighting
- ◆ Heating
- ◆ Static switching

Features

- ◆ Blocking voltage to 600 V
- ◆ On-state RMS current to 8 A

SYMBOL	PARAMETER	Value	Unit
V_{DRM}	Repetitive peak off-state voltages	600	V
$I_T (RMS)$	RMS on-state current (full sine wave)	8	A
I_{TSM}	Non-repetitive peak on-state current (full cycle, T_j initial=25°C)	84	A

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$R_{th(j-c)}$	Junction to case(AC)		-	1.6	-	°C/W
$R_{th(j-a)}$	Junction to ambient		-	70	-	°C/W

Limiting values in accordance with the Maximum system(IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN	Value	UNIT
V_{DRM}/V_{RRM}	Repetitive peak off-state Voltages		-	600	V
$I_{T(RMS)}$	RMS on-state current	Full sine wave; $T_c=110^{\circ}\text{C}$	-	8	A
I_{TSM}	Non repetitive surge peak on-state current	full cycle, T_j initial= 25°C			
		F=50Hz t=20ms	-	80	A
		F=60Hz t=16.7ms	-	84	A
I^2t	I^2t value for fusing	tp=10ms	-	36	A ² S
di/dt	Critical rate of rise of on-state current	$I_G=2 \times I_{GT}$, tr<=100ns F=120Hz $T_j=125^{\circ}\text{C}$	-	50	A/ μs
I_{GM}	Peak gate current	tp=20us $T_j=125^{\circ}\text{C}$	-	4	A
I_{DRM}	$V_{DRM}=V_{RRM}$	$T_j=25^{\circ}\text{C}$	-	5	μA
I_{RRM}		$T_j=125^{\circ}\text{C}$	-	1	mA
$P_{G(AV)}$	Average gate power dissipation	$T_j=125^{\circ}\text{C}$	-	1	W
T_{stg}	Storage junction temperature range		-40	150	$^{\circ}\text{C}$
T_j	Operating junction temperature range		-40	125	$^{\circ}\text{C}$

$T_j=25^{\circ}\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
Static characteristics						
$I_{GT}(1)$		$V_D=12\text{V}; R_L=30\Omega$	-	-	10	mA
V_{GT}		I-II-III			1.3	V
I_L		$I_G=1.2 I_{GT}$	-	-	25	mA
		I-III			30	mA
$I_H(2)$		$I_T=100\text{mA}$	-	-	15	mA
V_{GD}		$V_D=V_{DRM}$ $R_L=3.3\text{K}\Omega$ $T_j=125^{\circ}\text{C}$	0.2	-	-	V
dV/dt(2)		$V_D=67\% V_{DRM}$ gate open; $T_j=125^{\circ}\text{C}$	40	-	-	V/ μs
(di/dt)c(2)		(dv/dt)c=0.1V/ μS $T_j=125^{\circ}\text{C}$ (dv/dt)c=10V/ μS $T_j=125^{\circ}\text{C}$	5.4 2.8	-	-	V/ μs

Dynamic Characteristics

$V_{TM}(2)$	$I_{TM}=11\text{A}$ tp=380 μs	$T_j=25^{\circ}\text{C}$	-	-	1.55	V
$V_{to}(2)$	Threshold voltage	$T_j=125^{\circ}\text{C}$	-	-	0.85	V
$R_g(2)$	Dynamic resistance	$T_j=125^{\circ}\text{C}$	-	-	50	m Ω

Note1: minimum I_{GT} is guaranteed at 5% of I_{GT} max.

Note2: for both polarities of A2 referenced to A1.

HAOPIN MICROELECTRONICS CO.,LTD.

Description

Fig. 1: Maximum power dissipation versus RMS on-state current (full cycle).




Fig. 2-1: RMS on-state current versus case temperature (full cycle).




Fig. 2-2: RMS on-state current versus ambient temperature (printed circuit board FR4, copper thickness: 35μm), full cycle.




Fig. 3: Relative variation of thermal impedance versus pulse duration.




Fig. 4: On-state characteristics (maximum values).





Fig. 5: Surge peak on-state current versus number of cycles.



Description

Fig. 6: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$, and corresponding value of I^2t .




Fig. 7: Relative variation of gate trigger current, holding current and latching current versus junction temperature (typical values).




Fig. 8-1: Relative variation of critical rate of decrease of main current versus $(dV/dt)_c$ (typical values). Snubberless & Logic Level Types




Fig. 8-2: Relative variation of critical rate of decrease of main current versus $(dV/dt)_c$ (typical values). Standard Types




Fig. 9: Relative variation of critical rate of decrease of main current versus junction temperature.





Fig. 10: DPAK and D²PAK Thermal resistance junction to ambient versus copper surface under tab (printed circuit board FR4, copper thickness: 35 μm).





T810-600B

Three quadrant triacs

HAOPIN MICROELECTRONICS CO.,LTD.

MECHANICAL DATA

Dimensions in mm
Net Mass: 2 g